

Parker 451 TC

Tough Cover Wetline Hoses



Overview:

Hydraulic Hose and Fittings

For more than half a century, Parker Hannifin has been both a pioneer and leader in the hydraulic hose and fittings market. Parker Hose, gives you more choices than any other hose company...which only leaves you with one choice.

More Products... with the largest selection of hydraulic hose, pneumatic hose, and more fitting sizes and configurations than any other manufacturer, we have exactly what you need.



Contact Information:

Parker Hannifin Corporation
Hose Products Division
30240 Lakeland Blvd.
Wickliffe, Oh. 44092

Phone: 1-440-943-5700

Fax: 1-440-943-3129 c

www.parker.hose.com



Products Features and Benefits:

Features

- Parker hoses & fittings
- High Pressure Hose Parker 451TC Series
 - Tough Cover
 - Flexible
 - Constant pressure rating
- Suction Hose Parker 811 Series
 - Flexible
 - Durable
 - Helical reinforcing wire

Benefits

- 451TC features a specially formulated MSHA-accepted cover that offers exceptional protection from hose-to-hose or hose-to-object abrasion
- 451TC features a one-half S.A.E. 100R1 minimum bend radius, making installation in tight spaces fast and simple
- 451TC rated to 3,000 P.S.I. constant working pressure through all sizes
- 811 one-half S.A.E. 100R4 minimum bend radius
- 811 oil- and weather-resistant synthetic rubber cover
- 811 Series suitable for vacuum applications up to 28 in/Hg

ENGINEERING YOUR SUCCESS.

451TC and 451ST Hydraulic Hoses: abrasion resistance and versatility

Parker 451TC and 451ST hydraulic hoses are what to specify when abrasion resistance and ease of use are required. Plus, you can choose the cover that provides the abrasion resistance for your application.

- **Tough Cover** — 451TC features a specially formulated MSHA-accepted cover that offers exceptional protection from hose-to-hose or hose-to-object abrasion. Hose lines last longer, minimizing maintenance and down time.
- **Super Tough cover** — When only maximum abrasion resistance will do, specify 451ST with the polymeric cover.
- **Flexible** — 451 features a one-half SAE 100R1 minimum bend radius, making installation in tight spaces fast and simple.
- **Constant pressure rating in all sizes** — With a 3,000 psi constant working pressure through all sizes, 451 is the one hose you can specify to cover almost every hydraulic application. So you can stock fewer hose types and simplify your inventory.



Construction

Synthetic rubber tube compatible with most petroleum-base hydraulic fluids; high-tensile steel wire reinforcement; and an oil-, weather-, and an abrasion-resistant black synthetic MSHA-accepted rubber cover or a high abrasion-resistant polymeric cover.

Applications and temperature ranges

- Most petroleum-based hydraulic fluids and lubrication oils within a temperature range of -40°F to +212°F (-40°C to +100°C).
- Water, water/oil emulsion, and water/glycol hydraulic fluids up to +185°F (+85°C).
- Air up to +158°F (+70°C).

Parkrimp compatible

Parker 43 Series crimp fittings, 451TC hose, and 451ST hose are compatible with the Parkrimp system of crimpers. So assembly is as simple as 1-2-3.



# Part Number	Hose I.D.		Hose O.D.		Maximum Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Weight		Crimp Fitting Series	
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	kg/m		
451TC-4	451ST-4	1/4	6,3	0.52	13	3000	21,0	12000	84,0	2	50	0.16	0,24	43
451TC-6	451ST-6	3/8	10	0.68	17	3000	21,0	12000	84,0	2 1/2	65	0.23	0,34	43
451TC-8	451ST-8	1/2	12,5	0.80	20	3000	21,0	12000	84,0	3 1/2	90	0.35	0,52	43
451TC-10	451ST-10	5/8	16	0.94	24	3000	21,0	12000	84,0	4	100	0.44	0,66	43
451TC-12	451ST-12	3/4	19	1.09	28	3000	21,0	12000	84,0	4 3/4	120	0.58	0,86	43
451TC-16	451ST-16	1	25	1.40	36	3000	21,0	12000	84,0	6	150	0.79	1,17	43
451TC-20*	451ST-20*	1 1/4	31,5	1.85	47	3000	21,0	12000	84,0	8 1/4	210	1.50	2,23	43

NOTE: The silver die ring must be used when crimping 43 Series Parkrimp fittings onto 451TC and 451ST hoses.

*-20 sizes must use Karrykrimp 2, Superkrimp, Parkrimp 2, or PHastkrimp.

DANGER

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

Before selecting or using any Parker hose or fittings or related accessories, it is important that you read and follow Parker Safety Guide for Selecting and Using Hoses, Fittings, and Related Accessories (Parker Publication No. 4400-B.1).

Distributed by:

Parke Value Added Service Center

Austin, Tx. 78754
Phone: 877-482-4899
Fax: 512-926-9333
www.phtruck.com

The World Standard



©2001 Parker Hannifin Corporation